Code

Remember to clear your browser cache before downloading :)

- GUI code (Perl for quagga)
- monitor (Perl. Can be used with Asterisk, GnuGK, Cisco (you can use Cisco for CO-BGP instead of quagga), Yate. Can be easily extended.)
- monitor (TCL, can be run by Embedded Event Manager (EEM)) EEM mini-howto
- CHF code (Perl. The code implements the lookup function and the “glue” to make it work with Asterisk.) Note: You must also have the monitor script (the previous bullet) running with subroutine write_plaintext. It will populate an intermediate CO-table (at the moment a plain text file “COtable.txt”, you can easily make it use a database also). The CHF will use the intermediate table instead of the CO-BGP table directly (Option 6).
- CHF code (C. Implements the lookup function, as well as Asterisk FastAGI “bindings”.). Note: You must also have the monitor script (the previous bullet) running with subroutine write_plaintext. It will populate an intermediate CO-table (at the moment a plain text file “COtable.txt”, you can easily make it use a database also). The CHF will use the intermediate table instead of the CO-BGP table directly.
- Convert an IPv6 prefix to a telephony prefix (and vice versa; Perl)

Configuration

Asterisk (tested in Linux Debian 6.0)

- sip.conf
- h323.conf
- extensions.conf
- modules.conf

GnuGK (tested in Linux Debian 6.0)

- See guidelines in the comments of the monitor code (above subroutine write_gnugk).

Yate (tested in Linux Debian 6.0)

- See guidelines from the monitor code (above subroutine write_yate).

Cisco ISR 2921

- Cisco ISR BGP configuration. NOTE: In this configuration the CO-BGP neighbor (in this example `10.10.5.12`) and the “normal” eBGP neighbor (`10.63.0.2`) are handled from the same router. In other words, **no dedicated “CO-BGP router” is needed**.
- Cisco ISR voice configuration example.

Quagga

Debian (in this example configuration, CO-BGP and the “normal” BGP are handled from the same process):

- /etc/quagga/bgpd.conf
- /etc/network/interfaces
- /etc/quagga/debian.conf
- /etc/quagga/zebra.conf

CentOS: Same as with Debian.

Note that no IPv4 networks are advertised to CO-BGP neighbor (10.10.0.12), and no IPv6 networks to CL-BGP neighbor (10.63.0.1):

```
# vtysh -c 'show ip bgp neighbors 10.63.0.1 advertised-routes'
> 10.10.5.0/24     10.63.0.2     0     32768 i
# vtysh -c 'show ipv6 bgp neighbors 10.63.0.1 advertised-routes'
% No such neighbor or address family
# vtysh -c 'show ip bgp neighbors 10.10.0.12 advertised-routes'
# vtysh -c 'show ipv6 bgp neighbors 10.10.0.12 advertised-routes'
*&gt; 2001:db8:941:215::/64
2001:db8::10:10:5:12
                                          0 32768 i
```

(Scipts, configuration and documentation by Visa Holopainen -2013)

From:
https://milcom.comnet.aalto.fi/ - **Comnet Milcom Document Server**

Permanent link:
https://milcom.comnet.aalto.fi/cobgp/v2013?rev=1380544721

Last update: **2013-09-30T12:38**